



300 HDIR

RADIOMETRIC CAPABILITIES IN HD RESOLUTION

- High Definition IR 1024x768 pixels
- Full HD TV 1080p

Two unique sensors combined into a compact Dual Camera platform.

Ideal for temperature measurement applications.



300 HDIR

Gyro Stabilized Gimbal

For Stable Imaging a fully digital 4-axis active gyro stabilization system compensate for the aircraft movements and vibrations.

Reliability and Lightweight

In order to insure a reliable and lightweight gimbal platform, the Swesystem solution is designed and manufactured using an aluminum structure combined with composite covers.

Superior Performance using Long Wave Thermal IR

High precision measurement accuracy, superb image quality and long wave solar reflection immunity provides outstanding performance for most applications.

Thermal Radiometric Output

The Radiometric output provides full thermal resolution images with real time temperature measurement for efficient Thermal inspections.

GPS tagging

All images are tagged with GPS data for Geo-reference.



A good choice for Power Line Inspection, Fire Mapping and Pipeline Inspection.

Responsive and accurate control



www.swesystem.se * info@swesystem.se * Phone: +46 (0) 16 708 60 * Fax: +46 (0) 16 705 04 * Stationsvägen 46 640 43, Ärla, Sweden

Copyright © 2007-2014 Swesystem. All rights reserved. All specifications are typical and subject to change without notice.

Please contact EKLUND INFRARED Inc., your US SweSystem Representative, for more information and pricing. 2985 Gordy Parkway, Marietta, GA 30066.

Email: info@eklundir.com. Phone 770-578-4435. Fax: 770-578-9899. Website: www.eklundir.com



300 HDIR Technical

Gimbal System

Type: Four Axis Active Gyro Stabilized Gimbal
Stabilization: $\approx 15 \mu\text{Rad}$
Coverage Az: 360° continuous
Coverage El: $+90^\circ$ to -120°
Dimension: $\varnothing 300 \text{ mm}$ (11.8")
Weight: 17kg (37lb)
Power: 20-30VDC, 250W

Thermal IR Camera

Array Size: 1024x768 pixels
Lens: $12^\circ \times 16^\circ$ (optional $24^\circ \times 32^\circ$)
Detector: Micro bolometer FPA
Spectral Range: 7.5-14 μm
Thermal sensitivity: $<0.05\text{K}$
Focus: Manual and Auto Focus
Digital Zoom: Yes
Temp Accuracy: $\pm 1.5^\circ\text{C}$, ($\pm 1.5\%$ of reading)

Daylight TV Camera

Type: Full HD 1080p
Image Sensor: 1/2.8" CMOS
Number of pixels: $\approx 2,38$ Megapixels
Optical Zoom: 30x (60° to 2°)
Digital Zoom: Yes

Accessories

Standard Config: Turret Camera Unit, Hand Control Unit, Interface Unit, Cable Kit.
Optional: Radiometric Package including Report generating Software.
IMU/INS for GEO reference capabilities.
Installation Kit: Available for most helicopter types, please enquire.

